

# ARAUCOPLY®

Home | AraucoPly | [Products](#) | [Certifications](#) | [Technical Information](#) | [Catalogs](#) | [Contact](#) | [Other Countries](#)

▼ Sanded

▶ Beaded

▶ Siding Products



## ARAUCOPLY® SANDED PANELS

are laid up on a composed core using exterior PF resin and 100% plantation grown Radiata pine for consistent quality and performance. Our face veneers are peeled from pruned logs - making AraucoPly Sanded panels one of the highest-graded AC products on the market today.

### PRODUCT FEATURES

AraucoPly® Sanded Panels are finished with 150-grit sandpaper on the face and 120-grit sandpaper on the back, facilitating easy finishing with excellent results. All grade-stamped AraucoPly® Sanded Panels are manufactured in accordance with the US PS 1-09 product standard, and all ACX and BCX products are PS1-09 underlayment compliant and are edge stamped as such by TECO.

- 100% radiata pine.
- Stable composed core with minimum voids.
- High quality solid face.
- Ideal for interior and exterior applications
- Pre-sanded and ready to finish
- Allows a variety of finishes

#### - A Grades:

- No more than 6 wood patches
- No more than 6 synthetic repairs
- Small, wood-based putty repairs are allowed.

#### - B Grades:

- No more than 6 wood patches
- No more than 8 synthetic repairs
- Small, wood-based putty repairs are allowed.

#### Cp Grades:

- All type of repairs are accepted.
- Open defects are not accepted.

#### Applications:

- Staircases.
- Table and counter tops.
- Base panel for high-pressure lamination.
- General industrial applications.
- Cabinets and furniture.



- Underlayment.
- General DIY projects.

Available Thicknesses in 48" x 96"					
1/4"	11/32"	15/32"	19/32"	23/32"	31/32"

[technical information](#) ▶



| [Contact](#)

| [Site Map](#)